

OFF ROAD MAXIMUM TRACTION



ADVENTURO M/T

Adventuro M/T is a maximum traction mud terrain tire for light trucks and SUV's. Featuring a traditional tread design with large, aggressive tread blocks, it provides superb traction on rough and muddy terrain. The Adventuro M/T also features reinforced casing construction for added durability.



15 - 16 Inch

Speed Rating: Q / S

70 / 75 / 85 Series

M + S

Features

Benefits

- Aggressive pattern design > Outstanding traction in all weather conditions
- High void ratio and pyramidal shaped tread elements > Excellent resistance to hydroplaning and capacity
- Special casing profile and solid shoulder pattern > Enhanced traction and cornering
- Reinforced casing construction > Superior overall resistance to damage

ADVENTURO M/T

OFF ROAD MAXIMUM TRACTION



Tire Size	LI / SR (s/d)	LR / PR	Item Number	Measuring Rim	Rim Width Range	Max. Load (s/d)		Max. Pressure		Tread Depth		Overall Diameter		Section Width		Weight		Side Wall
				inch	inch	lbs	kg	psi	kpa	32 nd	mm	inch	mm	inch	mm	lbs	kg	
31X10.50R15LT	109Q	C / 6	100A1772	8.5	7.5 - 9.0	2270	1030	51	350	18	14.6	30.7	781	10.6	268	43.2	19.6	OWL
33X12.50R15LT	108Q	C / 6	100A1774	10.0	8.0 - 11.0	2205	1000	36	250	18	14.6	32.8	832	12.5	318	53.1	24.1	OWL
LT235/75R15	104/101S	C / 6	100A1771	6.5	6.0 - 7.0	1985/1820	900/825	51	350	18	14.6	29.1	739	9.3	235	37.9	17.2	OWL
LT305/70R16	118/115Q	D / 8	100A1776	9.0	8.5 - 9.5	2910/2680	1320/1215	51	350	18	14.6	33.1	840	12.2	311	53.4	24.2	OWL
LT225/75R16	115/112Q	E / 10	100A1341	6.0	6.0 - 7.0	2680/2470	1215/1120	80	550	16	12.6	29.5	750	8.8	223	38.0	17.2	OWL
LT245/75R16	120/116Q	E / 10	100A1770	7.0	6.5 - 7.5	3042/2778	1380/1260	80	550	18	14.6	30.7	780	9.8	248	44.2	20.1	OWL
LT265/75R16	123/120Q	E / 10	100A1777	7.5	7.0 - 8.0	3415/3085	1550/1400	80	550	18	14.6	31.9	810	10.5	267	47.4	21.5	OWL
LT285/75R16	122/119Q	D / 8	100A1775	8.0	7.5 - 8.5	3305/3000	1500/1360	65	450	18	14.6	33.1	840	11.3	286	54.4	24.7	OWL
LT235/85R16	120/116Q	E / 10	100A1773	6.5	6.0 - 7.0	3042/2778	1380/1260	80	550	18	14.6	32.0	812	9.3	235	45.8	20.8	OWL

LI Load Index SR Speed Rating LR Load Range PR Ply Rating (s/d) Single/Dual OWL Outline White Letter