

STUDDABLE WINTER



Studdable



CHAMPIRO IcePro



Comfort



Studdable



Directional



Winter



5
5 Year Limited
Warranty

Champiro IcePro is a studdable winter tire with sizes for passenger and crossover vehicles. Designed to handle the harshest

ice and snow conditions, it can be used with or without studs, depending on the level of traction required.



13 - 18 Inch



Speed Rating: T



45 - 75 Series

M + S

Features

Innovative studdable design

Specially designed stud distribution

Wide groove tread design

Silica compound

Benefits

Delivers reliability in extreme weather conditions

Enhances grip and reduces noise levels

Effectively removes slush and ice from tread contact area

Improves ice performance and snow traction

CHAMPIRO IcePro

STUDDABLE WINTER



Tire Size	LI / SR	Item Number	Measuring Rim	Rim Width Range	Max. Load		Max. Pressure		Tread Depth		Overall Diameter		Section Width		Weight		Side Wall
			inch	inch	lbs	kg	psi	kpa	32 nd	mm	inch	mm	inch	mm	lbs	kg	
155/70R13	75T	100A1667	4.5	4.0 - 5.0	853	387	44	300	12	9.2	21.6	548	6.2	157	13.4	6.1	BSW
175/70R13	82T	100A1664	5.0	4.5 - 6.0	1047	475	44	300	12	9.7	22.7	576	7.0	177	15.9	7.2	BSW
185/60R14	82T	100A1983	5.5	5.0 - 6.5	1047	475	44	300	12	9.7	22.8	578	7.4	189	17.2	7.8	BSW
185/55R15	86T XL	100A1984	6.0	5.0 - 6.5	1168	530	50	340	12	9.7	23.0	585	7.6	194	19.0	8.6	BSW
195/55R15	89T XL	100A1985	6.0	5.5 - 7.0	1279	580	50	340	12	9.7	23.4	595	7.9	201	20.4	9.3	BSW
205/65R15	94T	100A195	6.0	5.5 - 7.0	1477	670	44	300	12	9.7	25.5	647	8.2	209	23.4	10.6	BSW
205/70R15	96T	100A198	6.0	5.5 - 7.0	1565	710	44	300	12	9.7	26.3	669	8.2	209	24.2	11.0	BSW
205/75R15	97T	100A1986	5.5	5.0 - 7.0	1609	730	44	300	12	9.7	27.1	689	8.0	203	23.9	10.8	BSW
225/55R16	99T XL	100A1987	7.0	6.0 - 8.0	1709	775	50	340	13	10.2	25.7	654	9.2	233	25.3	11.5	BSW
225/65R16	100T	100A1670	6.5	6.0 - 8.0	1764	800	44	300	13	10.2	27.5	698	9.0	228	27.9	12.6	BSW
235/45R17	97T XL	100A1989	8.0	7.5 - 9.0	1609	730	50	340	12	9.7	25.4	644	9.3	236	25.9	11.8	BSW
225/55R18	98T	100A1990	7.0	6.0 - 8.0	1653	750	44	300	13	10.2	27.8	705	9.2	233	27.4	12.4	BSW

LI Load Index SR Speed Rating XL Extra Load BSW Black Side Wall

