

STUDDABLE WINTER


Studdable




CHAMPRO IcePro

Designed to provide excellent grip and handling in extreme winter weather conditions.



 13 - 18 Inch

 Speed Rating: T

 45 - 75 Series

M + S

Features Benefits

- | | | |
|--------------------------------------|---|---|
| Innovative studdable design | > | Reliable in extreme weather conditions |
| Specially designed stud distribution | > | Enhances grip and reduces noise levels |
| Wide groove tread design | > | Effectively removes slush and ice from the contact area |
| Silica compound | > | Enhances ice performance and snow traction |

CHAMPIRO IcePro

STUDDABLE WINTER



Tire Size	LI / SR	Item Number	Measuring Rim	Rim Width Range	Max. Load		Max. Pressure		Tread Depth		Overall Diameter		Section Width		Weight		Side Wall
			inch	inch	lbs	kg	psi	kpa	32 nd	mm	inch	mm	inch	mm	lbs	kg	
155/70R13	75T	100A1667	4.5	4.0 - 5.0	853	387	44	300	12	9.2	21.6	548	6.2	157	13.4	6.1	BSW
175/70R13	82T	100A1664	5.0	4.5 - 6.0	1047	475	44	300	12	9.7	22.7	576	7.0	177	15.9	7.2	BSW
185/60R14	82T	100A1983	5.5	5.0 - 6.5	1047	475	44	300	12	9.7	22.8	578	7.4	189	17.2	7.8	BSW
175/65R14	86T XL	100A1497	5.0	5.0 - 6.0	1168	530	50	340	12	9.2	23.0	584	7.0	177	16.9	7.7	BSW
185/65R14	90T XL	100A1499	5.5	5.0 - 6.0	1323	600	50	340	12	9.7	23.5	596	7.4	189	18.5	8.4	BSW
175/70R14	84T	100A1787	5.0	4.5 - 6.0	1102	500	44	300	12	9.2	23.7	602	7.0	177	16.9	7.7	BSW
185/70R14	88T	100A1666	5.5	4.5 - 6.0	1235	560	44	300	12	9.7	24.3	616	7.4	189	18.7	8.5	BSW
185/55R15	86T XL	100A1984	6.0	5.0 - 6.5	1168	530	50	340	12	9.7	23.0	585	7.6	194	19.0	8.6	BSW
195/55R15	89T XL	100A1985	6.0	5.5 - 7.0	1279	580	50	340	12	9.7	23.4	595	7.9	201	20.4	9.3	BSW
185/60R15	84T	100A196	5.5	5.0 - 6.0	1102	500	44	300	12	9.7	23.7	603	7.4	189	18.9	8.6	BSW
195/60R15	88T	100A188	6.0	5.5 - 7.0	1235	560	44	300	12	9.7	24.2	615	7.9	201	19.0	8.6	BSW
185/65R15	92T XL	100A1500	5.5	5.0 - 6.0	1389	630	50	340	12	9.7	24.4	621	7.4	189	20.9	9.5	BSW
195/65R15	95T XL	100A1498	6.0	5.5 - 6.5	1521	690	50	340	12	9.7	25.0	635	7.9	201	21.4	9.7	BSW
205/65R15	94T	100A195	6.0	5.5 - 7.0	1477	670	44	300	12	9.7	25.5	647	8.2	209	23.4	10.6	BSW
205/70R15	96T	100A198	6.0	5.5 - 7.0	1565	710	44	300	12	9.7	26.3	669	8.2	209	24.2	11.0	BSW
205/75R15	97T	100A1986	5.5	5.0 - 7.0	1609	730	44	300	12	9.7	27.1	689	8.0	203	23.9	10.8	BSW
205/55R16	94T XL	100A1496	6.5	6.0 - 7.0	1477	670	50	340	12	9.7	24.9	632	8.4	214	22.6	10.2	BSW
215/55R16	97T XL	100A1668	7.0	6.0 - 7.5	1609	730	50	340	13	10.2	25.3	642	8.9	226	23.2	10.5	BSW
225/55R16	99T XL	100A1987	7.0	6.0 - 8.0	1709	775	50	340	13	10.2	25.7	654	9.2	233	25.3	11.5	BSW
205/60R16	96T XL	100A1502	6.0	5.5 - 6.5	1565	710	50	340	12	9.7	25.7	652	8.2	209	23.6	10.7	BSW
215/60R16	95T	100A192	6.5	5.5 - 7.0	1521	690	44	300	12	9.7	26.1	664	8.7	221	24.9	11.3	BSW
225/60R16	98T	100A190	6.5	6.0 - 7.5	1653	750	44	300	12	9.7	26.6	676	9.0	228	26.5	12.0	BSW
215/65R16	102T XL	100A1501	6.5	6.0 - 7.0	1874	850	50	340	12	9.7	27.0	686	8.7	221	26.1	11.9	BSW
225/65R16	100T	100A1670	6.5	6.0 - 8.0	1764	800	44	300	13	10.2	27.5	698	9.0	228	27.9	12.6	BSW
225/45R17	94T XL	100A1665	7.5	7.0 - 8.5	1477	670	50	340	13	10.2	25.0	634	8.9	225	23.6	10.7	BSW
235/45R17	97T XL	100A1989	8.0	7.5 - 9.0	1609	730	50	340	12	9.7	25.4	644	9.3	236	25.9	11.8	BSW
215/50R17	91T	100A1988	7.0	6.0 - 7.5	1356	615	44	300	12	9.7	25.5	648	8.9	226	23.2	10.5	BSW
225/50R17	94T	100A1669	7.0	6.0 - 8.0	1477	670	44	300	12	9.7	25.9	658	9.2	233	25.3	11.5	BSW
215/55R17	98T XL	100A1602	7.0	6.5 - 7.5	1653	750	50	340	12	9.7	26.3	668	8.9	226	25.2	11.4	BSW
225/55R17	97T	100A1788	7.0	6.0 - 8.0	1609	730	44	300	13	10.2	26.8	680	9.2	233	25.9	11.7	BSW
215/60R17	96T	100A199	6.5	5.5 - 7.0	1565	710	44	300	13	10.2	27.2	690	8.7	221	16.6	12.1	BSW
225/60R17	99T	100A193	6.5	6.0 - 7.5	1708	775	44	300	13	10.2	27.6	702	9.0	228	28.2	12.8	BSW
225/55R18	98T	100A1990	7.0	6.0 - 8.0	1653	750	44	300	13	10.2	27.8	705	9.2	233	27.4	12.4	BSW

LI Load Index SR Speed Rating XL Extra Load BSW Black Side Wall