


STUDLESS WINTER PERFORMANCE



CHAMPIRO WinterPro HP

WinterPro HP is GT Radial's Performance Winter tire developed to meet the needs of drivers who want to retain the handling and precision of their high and ultra high performance sports cars, sedans, or coupes during winter conditions.



 16 - 20 Inch

 Speed Rating: H / V

 40 - 65 Series

M + S

Features

Benefits

- | | |
|--|--|
| Asymmetric tread design | > Provides excellent performance during the varied winter conditions |
| Three wide circumferential tread grooves | > Helps evacuate water, slush and packed snow while maintaining maximum contact with the road |
| Unique lateral cross-cut groove | > Effectively disperses water and slush and provides more biting angles for improved snow and ice grip |
| Sunflower oil enriched compound | > Increases low temperature traction for improved wet braking and handling, and better snow performance |
| Ultra high performance platform design | > Provides the handling and precision demanded by owners of ultra high performance sports cars, sedans, or coupes during winter conditions |

CHAMPIRO WinterPro HP

STUDLESS WINTER PERFORMANCE



Tire Size	LI / SR	Item Number	Measuring Rim	Rim Width Range	Max. Load		Max. Pressure		Tread Depth		Overall Diameter		Section Width		Weight		Side Wall
			inch	inch	lbs	kg	psi	kpa	32 nd	mm	inch	mm	inch	mm	lbs	kg	
195/55R16	87H	A650	6.0	5.5 - 7.0	1201	545	44	300	11	8.8	24.4	620	7.9	201	20.0	9.1	BSW
205/55R16	94V XL	A588	6.5	5.5 - 7.5	1477	670	44	300	12	9.0	24.9	632	8.4	214	22.0	10.0	BSW
225/55R16	99V XL	A660	7.0	6.0 - 8.0	1709	775	49	340	12	9.1	25.7	654	9.2	233	24.3	11.0	BSW
235/60R16	100H	A634	7.0	6.5 - 8.5	1764	800	44	300	11	8.7	27.1	688	9.4	240	27.4	12.4	BSW
225/45R17	94V XL	A586	7.5	7.0 - 8.5	1477	670	44	300	12	9.0	25.0	634	8.9	225	22.2	10.1	BSW
235/45R17	97V XL	A607	8.0	7.5 - 9.0	1609	730	49	340	12	9.4	25.4	644	9.3	236	24.3	11.0	BSW
245/45R17	99V	A648	8.0	7.5 - 9.0	1709	775	49	340	11	8.7	25.7	652	9.6	243	26.6	12.1	BSW
205/50R17	93V XL	A605	6.5	5.5 - 7.5	1433	650	49	340	12	9.0	25.1	638	8.4	214	22.3	10.1	BSW
225/50R17	98V XL	A589	7.0	6.0 - 8.0	1653	750	49	340	12	9.0	25.9	658	9.2	233	25.7	11.7	BSW
215/55R17	98V XL	A608	7.0	6.0 - 7.5	1477	670	49	340	10	7.8	26.7	678	9.3	235	24.3	11.0	BSW
225/55R17	101V XL	A609	7.0	6.0 - 8.0	1819	825	49	340	12	9.1	26.8	680	9.2	233	26.0	11.8	BSW
235/55R17	103V XL	A610	7.5	6.5 - 8.5	1929	875	49	340	12	9.2	27.2	690	9.6	245	26.6	12.1	BSW
215/60R17	96H	A620	6.5	6.0 - 7.5	1565	710	44	300	11	8.7	27.2	690	8.7	221	25.4	11.5	BSW
225/60R17	99H	A621	6.5	6.0 - 8.0	1709	775	44	300	11	8.7	27.6	702	9.0	228	27.0	12.2	BSW
225/65R17	102H	A622	6.5	6.0 - 8.0	1874	850	44	300	11	8.7	28.5	724	9.0	228	27.5	12.5	BSW
235/65R17	108H XL	A647	7.0	6.5 - 8.5	2205	1000	49	340	11	8.7	29.1	738	9.4	240	29.1	13.2	BSW
225/40R18	92V XL	A595	8.0	7.5 - 9.0	1389	630	49	340	10	7.8	25.4	645	9.4	239	22.4	10.1	BSW
235/40R18	95V XL	A596	8.5	8.0 - 9.5	1389	630	49	340	10	7.8	25.7	653	9.9	251	24.9	11.3	BSW
245/40R18	97V XL	A594	8.5	8.0 - 9.5	1609	730	49	340	12	9.0	25.7	653	9.8	248	27.6	12.5	BSW
225/45R18	95V XL	A597	7.5	7.0 - 8.5	1356	615	44	300	10	7.8	26.3	667	9.2	234	25.5	11.6	BSW
245/45R18	100V XL	A649	8.0	7.5 - 9.0	1764	800	49	340	11	8.7	26.7	677	9.6	243	27.7	12.6	BSW
235/50R18	101V XL	A606	7.5	6.5 - 8.5	1819	825	49	340	10	7.8	27.7	703	10.0	255	27.2	12.4	BSW
235/55R18	104V XL	A612	7.5	6.5 - 8.5	1984	900	49	340	11	8.7	28.1	715	9.6	245	28.2	12.8	BSW
255/55R18	109V XL	A618	8.0	7.0 - 9.0	2271	1030	49	340	11	8.7	29.0	737	10.4	265	30.8	14.0	BSW
235/60R18	107H XL	A623	7.0	6.5 - 8.5	2149	975	49	340	11	8.7	29.1	739	9.4	240	29.7	13.5	BSW
255/60R18	112H XL	A624	7.5	7.0 - 9.0	2469	1120	49	340	11	8.7	30.0	763	10.2	260	32.4	14.7	BSW
255/50R19	107V XL	A590	8.0	7.0 - 9.0	2149	975	49	340	12	9.0	29.1	739	10.4	265	32.3	14.6	BSW
235/55R19	105H XL	A617	7.5	6.5 - 8.5	2039	925	49	340	11	8.7	29.2	741	9.6	245	29.6	13.4	BSW
255/55R19	111H XL	A619	8.0	7.0 - 9.0	2403	1090	49	340	11	8.7	30.0	763	10.4	265	33.8	15.3	BSW
275/40R20	106V XL	A591	9.5	9.0 - 11.0	2094	950	49	340	12	9.0	28.7	728	10.9	278	32.5	14.8	BSW
275/45R20	110V XL	A604	9.0	8.5 - 10.0	2094	950	49	340	10	8.0	29.8	756	10.7	273	34.5	15.7	BSW

LI Load Index SR Speed Rating XL Extra Load BSW Black Side Wall