


# STUDLESS WINTER





## CHAMPIRO WinterPro

Designed to provide optimal wet and ice performance.



 13 - 16 Inch

 Speed Rating: T / H

 50 / 55 / 60 / 65 / 70 / 80 Series

M + S

### Features

### Benefits

Directional winter tread design

> Enhanced road contact and performance for snow and wet road conditions

Optimized tread sipe design

> Enhanced acceleration and braking under winter conditions

Silica tread compound

> Enhanced traction on low friction surfaces and extreme temperatures for improved driver safety

**Champiro WinterPro delivers optimal wet and ice performance and retains excellent dry and snow performance**



WinterPro Special compound formula and unique pattern design for best performance on low temperature wet and ice properties around 0° C



Unique elliptic grooves work like a pump. The wider center removes the water which is pumped away through the narrow slant from the contact area.

# CHAMPIRO WinterPro

STUDLESS WINTER



Tire Size	LI / SR	Item Number	Measuring Rim	Rim Width Range	Max. Load		Max. Pressure		Tread Depth		Overall Diameter		Section Width		Weight		Side Wall
			inch	inch	lbs	kg	psi	kpa	32 <sup>nd</sup>	mm	inch	mm	inch	mm	lbs	kg	
145/70R13	71T	A863	4.5	3.5 - 5.0	761	345	35	240	12	9.0	21.0	534	5.9	150	12.6	5.7	BSW
155/70R13	75T	A888	4.5	4.0 - 5.0	853	387	35	240	12	9.0	21.6	548	6.2	157	13.5	6.1	BSW
165/70R13	79T	A889	5.0	4.0 - 5.5	963	437	35	240	12	9.0	22.1	562	6.5	166	14.8	6.7	BSW
175/70R13	82T	A859	5.0	4.5 - 6.0	1047	475	35	240	12	9.0	22.8	579	7.0	179	16.2	7.3	BSW
145/80R13	79T XL	A891	4.0	3.5 - 5.0	963	437	44	300	12	9.0	22.1	562	5.7	145	13.2	6.0	BSW
155/80R13	83T XL	A890	4.5	4.0 - 5.0	1074	487	44	300	12	9.0	22.8	578	6.2	158	14.1	6.4	BSW
185/60R14	82T	A481	5.5	5.0 - 6.5	1047	475	35	240	12	9.0	22.8	578	7.5	191	17.9	8.1	BSW
155/65R14	75T	A527	4.5	4.5 - 5.5	853	387	35	240	12	9.0	22.0	558	6.2	157	13.7	6.2	BSW
165/65R14	79T	A528	5.0	4.5 - 6.0	963	437	35	240	12	9.0	22.4	570	6.7	170	15.2	6.9	BSW
175/65R14	82T	A529	5.0	5.0 - 6.0	1047	475	35	240	12	9.0	23.0	584	7.0	177	16.7	7.6	BSW
175/65R14	86T XL	A659	5.0	5.0 - 6.0	1168	530	49	340	11	8.9	23.0	584	7.0	177	17.2	7.8	BSW
185/65R14	86T	A530	5.5	5.0 - 6.5	1168	530	35	240	12	9.0	23.5	596	7.4	188	18.5	8.4	BSW
165/70R14	81T	A860	5.0	4.0 - 5.5	1019	462	35	240	12	9.0	23.1	588	6.7	170	15.5	7.0	BSW
175/70R14	84T	A861	5.0	4.5 - 6.0	1102	500	35	240	12	9.0	23.7	602	7.0	177	17.4	7.9	BSW
185/70R14	88T	A862	5.5	4.5 - 6.0	1235	560	35	240	12	9.0	24.3	616	7.4	189	18.9	8.6	BSW
175/80R14	88T	A892	5.0	4.5 - 6.0	1235	560	35	240	12	9.0	25.0	636	6.9	176	18.5	8.4	BSW
195/50R15	82H	A480	6.0	5.5 - 7.0	1047	475	44	300	12	9.0	22.7	577	7.9	201	18.9	8.6	BSW
175/55R15	77T	A395	5.5	5.0 - 6.0	908	412	35	240	12	9.0	22.6	573	7.0	179	16.5	7.5	BSW
185/55R15	82T	A396	6.0	5.0 - 6.5	1047	475	35	240	12	9.0	23.0	585	7.6	194	17.6	8.0	BSW
185/55R15	86H XL	A397	6.0	5.0 - 6.5	1168	530	44	300	12	9.0	23.0	585	7.6	194	18.6	8.4	BSW
195/55R15	85H	A398	6.0	5.5 - 7.0	1135	515	44	300	12	9.0	23.4	595	7.9	201	19.5	8.9	BSW
155/60R15	74T	A482	4.5	4.5 - 5.5	826	375	35	240	12	9.0	22.3	567	6.2	157	13.7	6.2	BSW
185/60R15	84T	A483	5.5	5.0 - 6.5	1102	500	35	240	12	9.0	23.7	603	7.4	189	19.9	9.0	BSW
185/60R15	88T XL	A484	5.5	5.0 - 6.5	1235	560	49	340	15	12.0	23.7	603	7.4	189	19.9	9.0	BSW
195/60R15	88T	A485	6.0	5.5 - 7.0	1235	560	35	240	12	9.0	24.2	615	7.9	201	20.5	9.3	BSW
175/65R15	84T	A854	5.0	5.0 - 6.0	1102	500	35	240	12	9.0	24.0	609	7.0	177	17.6	8.0	BSW
185/65R15	88T	A658	5.5	5.0 - 6.5	1235	560	44	300	12	9.0	24.4	621	7.4	189	19.5	8.9	BSW
195/65R15	91T	A855	6.0	5.5 - 7.0	1356	615	35	240	12	9.0	25.0	635	21.3	541	21.5	9.8	BSW
195/65R15	95T XL	A856	6.0	5.5 - 7.0	1521	690	45	300	12	9.0	25.0	635	8.0	203	21.5	9.8	BSW
195/65R15	91H	A657	6.0	5.5 - 7.0	1356	615	44	300	15	12.0	25.0	635	7.9	201	21.2	9.6	BSW
205/65R15	94T	A857	6.0	5.5 - 7.5	1477	670	35	240	12	9.0	25.5	647	8.2	209	24.0	10.9	BSW
205/55R16	91T	A399	6.5	5.5 - 7.5	1356	615	35	240	15	12.0	24.9	632	8.3	210	21.5	9.8	BSW
205/55R16	91H	A656	6.5	5.5 - 7.5	1356	615	44	300	11	8.9	24.9	632	8.4	214	22.0	10.0	BSW
205/55R16	94H XL	A400	6.5	5.5 - 7.5	1477	670	49	340	12	9.0	24.9	632	8.3	210	21.5	9.8	BSW
215/55R16	93H	A401	7.0	6.0 - 7.5	1433	650	44	300	12	9.0	25.3	642	8.9	226	22.6	10.3	BSW
215/55R16	97H XL	A477	7.0	6.0 - 7.5	1609	730	49	340	12	9.0	25.3	642	8.9	226	25.6	11.6	BSW
225/55R16	95H	A478	7.0	6.0 - 8.0	1521	690	44	300	12	9.0	25.7	654	9.2	233	27.1	12.3	BSW
225/55R16	99H XL	A479	7.0	6.0 - 8.0	1709	775	49	340	12	9.0	25.7	654	9.2	233	24.7	11.2	BSW
195/60R16	89H	A486	6.0	5.5 - 7.0	1279	580	44	300	12	9.0	25.2	640	7.9	201	24.7	11.2	BSW
205/60R16	92H	A487	6.0	5.5 - 7.5	1389	630	44	300	15	12.0	25.7	652	8.2	209	23.8	10.8	BSW
205/60R16	96H XL	A525	6.0	5.5 - 7.5	1565	710	49	340	12	9.0	25.7	652	8.2	209	23.8	10.8	BSW
215/60R16	99H XL	A526	6.5	6.0 - 7.5	1709	775	49	340	12	9.0	26.1	664	8.7	221	25.7	11.7	BSW
215/65R16	98H	A858	6.5	6.0 - 7.5	1653	750	44	300	12	9.0	27.0	686	8.9	225	25.9	11.8	BSW

LI Load Index SR Speed Rating XL Extra Load BSW Black Side Wall