


STUDDABLE WINTER


Studdable




ICEPRO³




ICEPRO³ is GT Radial's next generation studdable winter tire with coverage for a wide range of passenger and crossover vehicles. Improvements in stud pin hole design and distribution maximize ice traction while an

optimized tread pattern enhances grip and reduces noise generation. Designed to handle the harshest ice and snow conditions, the ICEPRO3 can be used with or without studs.

 14 - 17 Inch

 Speed Rating: T

 45 - 70 Series

M + S

Features

Benefits

New directional tread pattern

Provides exceptional grip and traction in deep snow and reduces road noise generation

Optimal distribution of up to 140 stud pin holes

Ensures maximum traction and shorter stopping distances on ice when tire studs are used

Wide groove tread design

Effectively removes slush and ice from tread contact area

High silica winter compound

Delivers excellent mileage and enhanced ice and snow performance in low temperatures

IcePro³

STUDDABLE WINTER



Tire Size	LI / SR	Item Number	Measuring Rim	Rim Width Range	Max. Load		Max. Pressure		Tread Depth		Overall Diameter		Section Width		Weight		Side Wall
			inch	inch	lbs	kg	psi	kpa	32 nd	mm	inch	mm	inch	mm	lbs	kg	
175/65R14	86T XL	100A3139	5.0	5.0 - 6.0	1168	530	50	340	11	9.1	23.0	584	7.0	177	17.6	8.0	BSW
185/65R14	90T XL	100A3142	5.5	5.0 - 6.5	1323	600	50	340	11	9.1	23.5	596	7.4	189	18.8	8.5	BSW
175/70R14	88T XL	100A3140	5.0	4.5 - 6.0	1235	560	50	340	11	9.1	23.7	602	7.0	177	18.5	8.4	BSW
185/70R14	92T XL	100A3144	5.5	4.5 - 6.0	1389	630	50	340	11	9.1	24.3	616	7.4	189	20.4	9.3	BSW
185/60R15	88T XL	100A3141	5.5	5.0 - 6.5	1235	560	50	340	11	9.1	23.7	603	7.4	189	19.6	8.9	BSW
195/60R15	92T XL	100A3145	6.0	5.5 - 7.0	1389	630	50	340	11	9.1	24.2	615	7.9	201	20.5	9.3	BSW
185/65R15	88T	100A3143	5.5	5.0 - 6.5	1235	560	44	300	11	9.1	24.5	621	7.4	189	18.5	8.4	BSW
195/65R15	95T XL	100A3146	6.0	5.5 - 7.0	1521	690	50	340	11	9.1	25.0	635	7.9	201	21.0	9.5	BSW
205/55R16	94T XL	100A3138	6.5	5.5 - 7.5	1477	670	50	340	11	9.1	24.9	632	8.4	214	21.8	9.9	BSW
215/55R16	97T XL	100A3149	7.0	6.0 - 7.5	1609	730	50	340	11	9.1	25.3	642	8.9	226	24.5	11.1	BSW
205/60R16	96T XL	100A3147	6.0	5.5 - 7.5	1565	710	50	340	11	9.1	25.7	652	8.2	209	23.4	10.6	BSW
215/60R16	99T XL	100A3151	6.5	6.0 - 7.5	1709	775	50	340	11	9.1	26.1	664	8.7	221	25.7	11.7	BSW
225/60R16	98T	100A3158	6.5	6.0 - 8.0	1653	750	44	300	11	9.1	26.6	676	9.0	228	25.2	11.4	BSW
205/65R16	95T	100A3159	6.0	5.5 - 7.5	1521	690	44	300	11	9.1	26.5	672	8.2	209	23.9	10.9	BSW
215/65R16	98T	100A3153	6.5	6.0 - 7.5	1653	750	44	300	11	9.1	27.0	686	8.7	221	25.2	11.4	BSW
225/45R17	94T XL	100A3154	7.5	7.0 - 8.5	1477	670	50	340	11	9.1	25.0	634	8.9	225	24.1	11.0	BSW
215/50R17	95T XL	100A3148	7.0	6.0 - 7.5	1521	690	50	340	11	9.1	25.5	648	8.9	226	23.8	10.8	BSW
225/50R17	98T XL	100A3155	7.0	6.0 - 8.0	1653	750	50	340	11	9.1	25.9	658	9.2	233	25.0	11.4	BSW
215/55R17	98T XL	100A3150	7.0	6.0 - 7.5	1653	750	50	340	11	9.1	26.3	668	8.9	226	26.1	11.8	BSW
225/55R17	101T XL	100A3156	7.0	6.0 - 8.0	1819	825	50	340	11	9.1	26.8	680	9.2	233	27.4	12.4	BSW
215/60R17	96T	100A3152	6.5	6.0 - 7.5	1565	710	44	300	11	9.1	27.2	690	8.7	221	25.3	11.5	BSW
225/60R17	99T	100A3157	6.5	6.0 - 8.0	1709	775	44	300	11	9.1	27.6	702	9.0	228	26.5	12.0	BSW

LI Load Index SR Speed Rating XL Extra Load BSW Black Side Wall

