


# STUDDABLE WINTER SUV & PICKUP TRUCK



## IcePro SUV<sup>3</sup>



ICEPRO SUV<sup>3</sup> is GT Radial's next generation studdable winter tire with sizes for pickup trucks and SUV's. It features a high-volume 150 pin hole distribution throughout the tread to maximize ice

traction and braking. ICEPRO SUV<sup>3</sup> can be used with or without studs and is designed to provide excellent grip and handling in extreme winter conditions while reducing on road noise.



16 - 18 Inch



Speed Rating: T



60 - 70 Series

M + S

### Features

### Benefits

Directional tread pattern designed specifically for SUV's

**Provides exceptional grip and traction in deep snow and reduces road noise generation**

Optimal distribution of up to 156 stud pin holes

**Ensures maximum traction and shorter stopping distances on ice when tire studs are used**

Wide groove tread design

**Effectively removes slush and ice from tread contact area**

High silica winter compound

**Delivers excellent mileage and enhanced ice and snow performance in low temperatures**

# IcePro SUV<sup>3</sup>

STUDDABLE WINTER SUV & PICKUP TRUCK



Tire Size	LI / SR	Item Number	Measuring Rim	Rim Width Range	Max. Load		Max. Pressure		Tread Depth		Overall Diameter		Section Width		Weight		Side Wall
			inch	inch	lbs	kg	psi	kpa	32 <sup>nd</sup>	mm	inch	mm	inch	mm	lbs	kg	
215/70R16	100T	100A3160	6.5	5.5 - 7.0	1764	800	44	300	12	9.2	27.9	708	8.7	221	27.5	12.5	BSW
235/70R16	109T XL	100A3165	7.0	6.0 - 8.0	2271	1030	50	340	12	9.2	29.0	736	9.5	240	32.4	14.7	BSW
225/65R17	102T	100A3161	6.5	6.0 - 8.0	1874	850	44	300	12	9.2	28.5	724	9.0	228	29.0	13.1	BSW
235/65R17	108T XL	100A3163	7.0	6.5 - 8.5	2205	1000	50	340	12	9.2	29.1	738	9.5	240	32.2	14.6	BSW
265/70R17	115T	100A3166	8.0	7.0 - 9.0	2679	1215	44	300	12	9.2	31.7	804	10.7	272	40.4	18.3	BSW
235/60R18	107T XL	100A3162	7.0	6.5 - 8.5	2149	975	50	340	12	9.2	29.1	739	9.5	240	31.8	14.4	BSW
245/60R18	105T	100A3167	7.0	7.0 - 8.5	2039	925	44	300	12	9.2	29.6	751	9.8	248	32.1	14.6	BSW
235/65R18	106T	100A3164	7.0	6.5 - 8.5	2094	950	44	300	12	9.2	30.0	763	9.5	240	32.3	14.7	BSW

**LI** Load Index   **SR** Speed Rating   **XL** Extra Load   **BSW** Black Side Wall

