

STUDLESS WINTER SUV



SAVERO WT



Savero WT is a studless winter tire made specifically for SUVs and crossover vehicles. It is designed to handle well in snow, slush, dirt,

mud, gravel rain and dry, and features durable construction for these vehicle applications.



15 - 17 Inch



Speed Rating: T



60 - 75 Series

M + S

Features

Benefits

Variable pitch directional tread pattern

Improves wet handling and gives a quieter ride

Aggressive circumferential tread grooves with slanted lateral grooves

Provide efficient self-cleaning function

Special low temperature tread compound

Enhance ice and snow driving performance

Continuous center rib

Provides good stability and steering response

Wave-shaped sipes

Improve traction on slippery surfaces

SAVERO WT

STUDLESS WINTER SUV



Tire Size	LI / SR	Item Number	Measuring Rim	Rim Width Range	Max. Load		Max. Pressure		Tread Depth		Overall Diameter		Section Width		Weight		Side Wall
			inch	inch	lbs	kg	psi	kpa	32 nd	mm	inch	mm	inch	mm	lbs	kg	
235/75R15	105T	100A341	6.5	6.0 - 8.0	2039	925	35	240	14	11.2	28.9	733	9.3	235	31.5	14.2	BSW
255/65R16	109T	100A358	7.5	7.0 - 9.0	2271	1030	35	240	14	11.2	29.1	738	10.2	260	35.3	16.6	BSW
225/70R16	103T	100A1051	6.5	6.0 - 7.5	1929	875	36	250	14	11.2	28.4	722	9.0	228	30.7	14.0	BSW
235/70R16	106T	100A1052	7.0	6.0 - 8.0	2094	950	36	250	14	11.2	29.0	736	9.4	240	33.6	15.3	BSW
245/70R16	107T	100A348	7.0	6.5 - 8.0	2149	975	35	240	14	11.2	29.5	750	9.8	248	37.3	17.2	BSW
255/70R16	111T	100A349	7.5	6.5 - 8.5	2403	1090	35	240	14	11.2	30.1	764	10.2	260	39.4	18.1	BSW
265/70R16	112T	100A353	8.0	7.0 - 9.0	2469	1120	35	240	14	11.2	30.6	778	10.7	272	40.8	18.6	BSW
225/75R16	104T	100A342	6.0	6.0 - 7.5	1984	900	35	240	14	10.8	29.3	744	9.0	228	31.1	14.1	BSW
245/75R16	111T	100A343	7.0	6.5 - 8.0	2403	1090	35	240	14	11.2	30.5	774	9.8	248	37.9	17.1	BSW
275/60R17	111T	100A359	8.0	7.5 - 9.5	2409	1060	35	240	14	11.2	30.0	762	11.0	279	42.4	19.3	BSW
245/65R17	107T	100A356	7.0	7.0 - 8.5	2149	975	35	240	14	11.2	29.7	753	9.8	248	37.0	17.0	BSW
265/70R17	115T	100A354	8.0	7.0 - 9.0	2679	1215	35	240	14	11.2	31.7	804	10.7	272	43.5	20.0	BSW

LI Load Index SR Speed Rating BSW Black Side Wall

