

# STUDLESS WINTER




## WINTERPRO<sup>2</sup>




WINTERPRO<sup>2</sup> is GT Radial's new studless winter tire with fitments for passenger and crossover vehicles. Featuring an innovative tread pattern

design and new tread compound, it is designed to provide optimal wet and ice performance and excel in snow and dry road conditions.

 13 - 17 Inch

 Speed Rating: T / H / V

 50 - 70 / 80 Series

M + S

### Features

### Benefits

New tread compound

Features Silica and Nanoscopic carbon black for improved ice, snow, wet braking and handling performance as well as lower rolling resistance and improved wear life

Directional tread design

Enhances traction, stability and directional control

Optimized variable pitch tread blocks

Reduce tread pattern noise for a quieter ride

Innovative sipe design

Featuring two types of tread sipe styles and alternating sipe depths improve snow performance and durability

Larger tread contact patch

Improves grip, handling and control

# WINTERPRO<sup>2</sup>

STUDLESS WINTER



Tire Size	LI / SR	Item Number	Measuring Rim	Rim Width Range	Max. Load		Max. Pressure		Tread Depth		Overall Diameter		Section Width		Weight		Side Wall
			inch	inch	lbs	kg	psi	kpa	32 <sup>nd</sup>	mm	inch	mm	inch	mm	lbs	kg	
155/70R13	75T	100A3186	4.5	4.0 - 5.0	853	387	44	300	11	8.5	21.6	548	6.2	157	12.9	5.9	BSW
165/70R13	79T	100A3189	5.0	4.0 - 5.5	963	437	44	300	11	8.5	22.1	562	6.7	170	14.1	6.4	BSW
155/80R13	79T	100A3193	4.5	4.0 - 5.0	963	437	44	300	11	8.5	22.8	578	6.2	157	13.8	6.3	BSW
185/60R14	82T	100A3179	5.5	5.0 - 6.5	1047	475	44	300	11	8.9	22.8	578	7.4	189	16.1	7.3	BSW
155/65R14	75T	100A3188	4.5	4.5 - 5.5	853	387	44	300	11	8.5	22.0	558	6.2	157	13.7	6.2	BSW
165/65R14	79T	100A3191	5.0	4.5 - 6.0	963	437	44	300	11	8.5	22.4	570	6.7	170	14.7	6.7	BSW
175/65R14	86T XL	100A3203	5.0	5.0 - 6.0	1168	530	50	340	11	8.9	23.0	584	7.0	177	16.4	7.5	BSW
185/65R14	86T	100A3182	5.5	5.0 - 6.5	1168	530	44	300	11	9.0	23.5	596	7.4	189	17.7	8.1	BSW
165/70R14	81T	100A3172	5.0	4.0 - 5.5	1019	462	44	300	11	8.5	23.1	588	6.7	170	15.0	6.8	BSW
195/50R15	82H	100A3201	6.0	5.5 - 7.0	1047	475	44	300	11	8.9	22.7	577	7.9	201	17.5	7.9	BSW
185/55R15	82T	100A3190	6.0	5.0 - 6.5	1047	475	44	300	11	8.9	23.0	585	7.6	194	17.2	7.8	BSW
195/55R15	85H	100A3195	6.0	5.5 - 7.0	1135	515	44	300	11	8.9	23.4	595	7.9	201	18.3	8.3	BSW
185/60R15	88T XL	100A3173	5.5	5.0 - 6.5	1235	560	50	340	11	8.9	23.7	603	7.4	189	17.3	7.8	BSW
195/60R15	88T	100A3185	6.0	5.5 - 7.0	1235	560	44	300	11	8.9	24.2	615	7.9	201	18.8	8.5	BSW
175/65R15	84T	100A3181	5.0	5.0 - 6.0	1102	500	44	300	11	8.9	24.0	609	7.0	177	16.8	7.6	BSW
185/65R15	88T	100A3169	5.5	5.0 - 6.5	1235	560	44	300	11	9.0	24.4	621	7.4	189	18.7	8.2	BSW
195/65R15	91H	100A3109	6.0	5.5 - 7.0	1356	615	44	300	11	8.7	25.0	635	7.9	201	19.9	8.6	BSW
205/65R15	94T	100A3198	6.0	5.5 - 7.5	1477	670	44	300	11	8.9	25.5	647	8.2	209	22.3	10.1	BSW
195/55R16	91H XL	100A3477	6.0	5.5 - 7.0	1356	615	50	340	11	8.7	24.4	620	7.9	201	18.8	8.5	BSW
205/55R16	91H	100A3168	6.5	5.5 - 7.5	1356	615	44	300	11	8.7	24.9	632	8.4	214	21.9	8.6	BSW
215/55R16	97H XL	100A3194	7.0	6.0 - 7.5	1609	730	50	340	11	8.9	25.3	642	8.9	226	23.6	10.7	BSW
225/55R16	99H XL	100A3196	7.0	6.0 - 8.0	1790	775	50	340	11	8.9	25.7	654	9.2	233	24.7	11.2	BSW
205/60R16	96H XL	100A3176	6.0	5.5 - 7.5	1565	710	50	340	11	8.7	25.7	652	8.2	209	20.9	9.5	BSW
215/60R16	99H XL	100A3175	6.5	6.0 - 7.5	1709	775	50	340	11	8.7	26.1	664	8.7	221	22.6	10.3	BSW
215/65R16	98H	100A3184	6.5	6.0 - 7.5	1653	750	44	300	11	9.1	27.0	686	8.7	221	25.0	11.4	BSW
215/70R16	100H	100A3205	6.5	5.5 - 7.0	1764	800	44	300	11	8.7	27.9	708	8.7	221	25.7	11.7	BSW
215/50R17	95V XL	100A3200	7.0	6.0 - 7.5	1521	690	50	340	11	8.7	25.5	648	8.9	226	23.8	10.8	BSW
205/55R17	95H XL	100A3202	6.5	5.5 - 7.5	1521	690	50	340	11	8.7	25.9	658	8.4	214	22.0	10.0	BSW
215/55R17	98V XL	100A3197	7.0	6.0 - 7.5	1653	750	50	340	11	8.7	26.3	668	8.9	226	23.5	10.7	BSW
235/65R17	108H XL	100A3478	7.0	6.5 - 8.5	2205	1000	50	340	11	9.1	29.1	738	9.5	240	30.2	13.7	BSW

LI Load Index    SR Speed Rating    XL Extra Load    BSW Black Side Wall

