

MAX PERFORMANCE SUMMER

CHAMPIRO HPY

SATISFACTION
30 DAY
TEST DRIVE
GUARANTEE



UHP



Asymmetrical



Agile Control
Dry/Wet



Handling




Low Noise



5
Year Limited
Warranty

Champiro HPY is a proven ultra-high performance summer tire designed to provide excellent control, turn-in and grip in the curves. With an asymmetrical

tread design, it also has great straight-line stability and a silica tread compound that performs in both wet and dry conditions.

 17 - 20 Inch

 Speed Rating: V / W / Y

 35 - 65 Series

UTQG: 300 AAA

Features

Benefits

Asymmetrical tread pattern design

Provides outstanding cornering on wet and dry surfaces

Solid center rib

Improves straight line stability and steering response

Four wide circumferential tread grooves

Enhances water evacuation for excellent hydroplaning resistance

Full silica tread compound

Improves grip on wet surfaces

CHAMPIRO HPY

MAX PERFORMANCE SUMMER



Tire Size	LI / SR	UTQG	Item Number	Measuring Rim	Rim Width Range	Max. Load		Max. Pressure		Tread Depth		Overall Diameter		Section Width		Weight		Side Wall
				inch	inch	lbs	kg	psi	kpa	32 nd	mm	inch	mm	inch	mm	lbs	kg	
245/40ZR17	95Y XL	300 AAA	B059	8.5	8.0 - 9.5	1521	690	49	340	10	7.8	24.7	628	9.8	248	25.5	11.6	BSW
255/40ZR17	98Y XL	300 AAA	B026	9.0	8.5 - 10.0	1653	750	49	340	10	7.8	25.0	636	10.2	260	26.3	11.9	BSW
205/45ZR17	88W XL	300 AAA	B349	7.0	6.5 - 7.5	1235	560	49	340	10	7.8	24.3	616	8.1	206	20.2	9.2	BSW
215/45ZR17	91Y XL	300 AAA	B058	7.0	7.0 - 8.0	1356	615	49	340	10	7.8	24.6	626	8.4	213	22.2	10.1	BSW
225/45ZR17	94Y XL	300 AAA	B057	7.5	7.0 - 8.5	1477	670	49	340	10	7.8	25.0	634	8.9	225	23.4	10.6	BSW
235/45ZR17	97Y XL	300 AAA	B046	8.0	7.5 - 9.0	1609	730	49	340	10	7.8	25.4	644	9.3	236	24.8	11.3	BSW
245/45ZR17	99Y XL	300 AAA	B045	8.0	7.5 - 9.0	1709	775	49	340	10	7.8	25.7	652	9.6	243	26.4	12.0	BSW
205/50ZR17	93W XL	300 AAA	B350	6.5	5.5 - 7.5	1433	650	49	340	10	7.8	25.1	638	8.4	214	21.8	9.9	BSW
225/50ZR17	98Y XL	300 AAA	B027	7.0	6.0 - 8.0	1653	750	49	340	10	7.8	25.9	658	9.2	233	26.1	11.8	BSW
235/50ZR17	100W XL	300 AAA	B028	7.5	6.5 - 8.5	1764	800	49	340	10	7.8	26.3	668	9.5	241	26.2	11.9	BSW
215/55ZR17	94W	300 AAA	B351	7.0	6.0 - 7.5	1477	670	44	300	10	7.8	26.3	668	8.9	226	23.6	10.7	BSW
225/65R17	102V	300 AAA	B347	6.5	6.0 - 8.0	1874	850	44	300	10	7.8	28.5	724	9.0	228	28.8	13.1	BSW
235/65R17	108V XL	300 AAA	B344	7.0	6.5 - 8.5	2205	1000	49	340	10	7.8	29.1	738	9.4	240	30.7	13.9	BSW
255/35ZR18	94Y XL	300 AAA	B030	9.0	8.5 - 10.0	1477	670	49	340	10	7.8	25.0	635	10.2	260	24.3	11.0	BSW
265/35ZR18	97Y XL	300 AAA	B048	9.5	9.0 - 10.5	1609	730	49	340	10	7.8	25.7	653	10.7	271	27.7	12.6	BSW
205/40ZR18	86Y XL	300 AAA	B352	7.5	7.0 - 8.0	1168	530	49	340	10	7.8	24.4	621	8.3	212	20.3	9.2	BSW
225/40ZR18	92Y XL	300 AAA	B023	8.0	7.5 - 9.0	1389	630	49	340	10	7.8	25.1	637	9.1	230	23.7	10.7	BSW
235/40ZR18	95Y XL	300 AAA	B022	8.5	8.0 - 9.5	1521	690	49	340	10	7.8	25.4	645	9.5	241	24.9	11.3	BSW
245/40ZR18	97Y XL	300 AAA	B024	8.5	8.0 - 9.5	1609	730	49	340	10	7.8	25.7	653	9.8	248	24.4	11.1	BSW
225/45ZR18	91Y	300 AAA	B054	7.5	7.0 - 8.5	1356	615	51	350	10	7.8	25.9	659	8.9	225	24.8	11.3	BSW
245/45ZR18	100Y XL	300 AAA	B029	8.0	7.5 - 9.0	1764	800	49	340	10	7.8	26.7	677	9.6	243	27.8	12.6	BSW
255/45ZR18	103Y XL	300 AAA	B055	8.5	8.0 - 9.5	1929	875	49	340	10	7.8	27.0	687	10.0	255	28.8	13.1	BSW
235/50ZR18	101Y XL	300 AAA	B056	7.5	6.5 - 8.5	1819	825	49	340	10	7.8	27.4	695	9.4	240	27.7	12.6	BSW
235/55ZR18	104W XL	300 AAA	B346	7.5	6.5 - 8.5	1984	900	49	340	10	7.8	28.1	715	9.6	245	29.3	13.3	BSW
255/55ZR18	109Y XL	300 AAA	B342	8.0	7.0 - 9.0	2271	1030	49	340	10	7.8	29.0	737	10.4	265	32.9	14.9	BSW
235/60R18	107V XL	300 AAA	B345	7.0	6.5 - 8.5	2149	975	49	340	10	7.8	29.1	739	9.4	240	30.4	13.8	BSW
225/35ZR19	88Y XL	300 AAA	B049	8.0	7.5 - 9.0	1235	560	49	340	10	7.8	25.2	641	9.1	230	23.3	10.6	BSW
235/35ZR19	91Y XL	300 AAA	B050	8.5	8.0 - 9.5	1356	615	49	340	10	7.8	25.5	647	9.5	241	24.2	11.0	BSW
255/35ZR19	96Y XL	300 AAA	B051	9.0	8.5 - 10.0	1565	710	49	340	10	7.8	26.0	661	10.2	260	27.5	12.5	BSW
225/40ZR19	93Y XL	300 AAA	B025	8.0	7.5 - 9.0	1433	650	49	340	10	7.8	26.1	663	9.1	230	23.0	10.4	BSW
255/40ZR19	96Y	300 AAA	B053	9.0	8.5 - 10.0	1565	710	51	350	10	7.8	27.0	687	10.2	260	29.5	13.4	BSW
255/50ZR19	107Y XL	300 AAA	B343	8.0	7.0 - 9.0	2149	975	49	340	10	7.8	29.1	739	10.4	265	32.8	14.9	BSW
255/35ZR20	97Y XL	300 AAA	B052	9.0	8.5 - 10.0	1609	730	49	340	10	7.8	27.0	686	10.2	260	28.8	13.1	BSW
255/45ZR20	101Y	300 AAA	B348	8.5	8.0 - 9.5	1819	825	44	300	10	7.8	29.1	738	10.0	255	32.0	14.5	BSW

LI Load Index SR Speed Rating XL Extra Load UTQG Uniform Tire Quality Grade BSW Black Side Wall

The CHAMPIRO HPY has an asymmetric tread design consisting of different inner and outer tread pattern and shoulder designs

The open inner shoulder with its continuous lateral grooves disperses water efficiently, providing excellent protection against hydroplaning.



Compact outer shoulder ensures optimum road contact and excellent cornering stability.