

ON / OFF ROAD ALL TERRAIN – ALL WEATHER



ADVENTURO AT-AW



Adventuro AT-AW is an all terrain tire developed for light truck drivers looking for off road capabilities and aggressive looks together with civilized on-road manners. Meeting the industry's severe snow service requirement

and branded with the mountain/snowflake symbol, the Adventuro AT-AW delivers "all weather" performance. All LT designation sizes feature heavy duty 10-ply construction.



16 - 18 / 20 Inch



Speed Rating: S / T



55 - 85 Series

UTQG: 500 A B

M + S

Features

Benefits

Enhanced tread compound

Provides excellent wet and dry grip, longer tread life, and improved cut/chip resistance

Optimized tread block design and siping

Delivers all weather traction for improved winter performance

3D grooves with chamfered edges

Results in self-cleaning tread design for consistent off-road performance, while reducing stone holding/drilling

Five-pitch pattern technology

Reduces road noise for a quieter, more comfortable ride

Rim protector

Helps protect wheel from curb damage

ADVENTURO AT-AW

ON / OFF ROAD ALL TERRAIN - ALL WEATHER



Tire Size	LI / SR	UTQG	Item Number	Measuring Rim	Rim Width Range	Max. Load		Max. Pressure		Tread Depth		Overall Diameter		Section Width		Weight		Side Wall
						lbs	kg	psi	kpa	32nd	mm	inch	mm	inch	mm	lbs	kg	
P275/65R18	114T	500 A B	100A2531	8.0	7.5 - 9.5	2601	1180	44	300	13	10.6	32.1	815	11.0	279	39.0	17.7	OWL
275/60R20	115T	500 A B	100A2534	8.0	7.5 - 9.5	2679	1215	44	300	13	10.6	33.0	838	11.0	279	41.8	19.0	BSW
275/55R20	113T	500 A B	100A2533	8.5	7.5 - 9.5	2535	1150	44	300	13	10.6	31.9	810	11.2	284	39.2	17.8	BSW

Tire Size	LI / SR (s/d)	LR/PR	Item Number	Measuring Rim	Rim Width Range	Max. Load (s/d)		Max. Pressure		Tread Depth		Overall Diameter		Section Width		Weight		Side Wall
						lbs	kg	psi	kpa	32nd	mm	inch	mm	inch	mm	lbs	kg	
LT225/75R16	115/112S	E / 10	100A2532	6.0	6.0 - 7.0	2680/2470	1215/1120	80	550	16	12.6	29.3	744	8.8	223	38.6	17.5	OWL
LT245/75R16	120/116S	E / 10	100A2528	7.0	6.5 - 8.0	3042/2778	1380/1260	80	550	16	12.6	30.5	774	9.8	248	42.5	19.3	OWL
LT265/75R16	123/120S	E / 10	100A2540	7.5	7.0 - 8.5	3415/3085	1550/1400	80	550	16	12.6	31.7	804	10.5	267	48.0	21.8	OWL
LT235/85R16	120/116S	E / 10	100A2539	6.5	6.0 - 7.5	3042/2778	1380/1260	80	550	16	12.6	31.7	806	9.3	235	43.1	19.5	BSW
LT245/70R17	119/116S	E / 10	100A2536	7.0	6.5 - 8.0	3000/2755	1360/1250	80	550	16	12.6	30.6	776	9.8	248	42.8	19.4	OWL
LT265/70R17	121/118S	E / 10	100A2527	8.0	7.0 - 8.5	3195/2910	1450/1320	80	550	16	12.6	31.7	804	10.7	272	47.7	21.6	OWL
LT285/70R17	121/118S	E / 10	100A2529	8.5	7.5 - 9.0	3195/2910	1450/1320	80	550	16	12.6	32.8	832	11.5	292	51.8	23.5	OWL
LT245/75R17	121/118S	E / 10	100A2538	7.0	6.5 - 7.5	3195/2910	1450/1320	80	550	16	12.6	31.5	800	9.8	248	44.6	20.2	OWL
LT235/80R17	120/117S	E / 10	100A2541	6.5	6.0 - 7.5	3085/2835	1400/1285	80	550	16	12.6	31.8	808	9.3	235	43.3	19.7	OWL
LT275/65R18	123/120S	E / 10	100A2530	8.0	7.5 - 9.0	3415/3085	1550/1400	80	550	16	12.6	32.1	815	11.0	279	49.1	22.3	OWL
LT265/70R18	124/121S	E / 10	100A2537	8.0	7.0 - 9.0	3525/3195	1600/1450	80	550	16	12.6	32.6	829	10.7	272	49.6	22.5	OWL
LT275/70R18	125/122S	E / 10	100A2535	8.0	7.0 - 8.5	3640/3305	1650/1500	80	550	16	12.6	33.2	843	11.0	279	51.3	23.3	OWL

LI Load Index SR Speed Rating UTQG Uniform Tire Quality Grade (s/d) Single/Dual LR Load Range PR Ply Rating BSW Black Side Wall OWL Outline White Letter

Enhanced Tread Compound — Provides longer tread life plus cut/chip resistance

Jointless Nylon Cap Ply — Stabilizes tire for greater control

Dual Steel Belts — Optimizes tread stiffness for improved handling

Durable Polyester Carcass — Maintains tread profile and minimizes deformation

Single Strand Bead Wire — Improves bead uniformity and durability

