

# OFF ROAD MAXIMUM TRACTION



## ADVENTURO M/T



Mud Terrain



Symmetrical



All Season



5 Year Limited Warranty

Adventure M/T is a maximum traction mud terrain tire for light trucks and SUV's. Featuring a traditional tread design with large, aggressive tread blocks, it provides superb traction on rough and

muddy terrain. The Adventure M/T also features reinforced casing construction for added durability.

 15 - 16 Inch

 Speed Rating: Q / S

 70 / 75 / 85 Series

M + S

### Features

### Benefits

Aggressive pattern design

Delivers outstanding traction in all weather conditions

High void ratio and pyramidal shaped tread elements

Provide excellent resistance to hydroplaning

Special casing profile and solid shoulder pattern

Enhance traction and cornering

Reinforced casing construction

Increases overall resistance to damage

# ADVENTURO M/T

OFF ROAD MAXIMUM TRACTION



Tire Size	LI / SR (s/d)	LR / PR	Item Number	Measuring	Rim Width	Max. Load		Max. Pressure		Tread Depth		Overall Diameter		Section Width		Weight		Side Wall
				Rim	Range	(s/d)	(s/d)	32 <sup>nd</sup>	mm	inch	mm	inch	mm	lbs	kg			
				inch	inch	lbs	kg	psi	kpa									
31X10.50R15LT	109Q	C / 6	100A1772	8.5	7.5 - 9.0	2270	1030	51	350	18	14.6	30.7	781	10.6	268	43.2	19.6	OWL
33X12.50R15LT	108Q	C / 6	100A1774	10.0	8.0 - 11.0	2205	1000	36	250	18	14.6	32.8	832	12.5	318	53.1	24.1	OWL
LT235/75R15	104/101S	C / 6	100A1771	6.5	6.0 - 7.0	1985/1820	900/825	51	350	18	14.6	29.1	739	9.3	235	37.9	17.2	OWL
LT305/70R16	118/115Q	D / 8	100A1776	9.0	8.5 - 9.5	2910/2680	1320/1215	51	350	18	14.6	33.1	840	12.2	311	53.4	24.2	OWL
LT225/75R16	115/112Q	E / 10	100A1341	6.0	6.0 - 7.0	2680/2470	1215/1120	80	550	16	12.6	29.5	750	8.8	223	38.0	17.2	OWL
LT245/75R16	120/116Q	E / 10	100A1770	7.0	6.5 - 7.5	3042/2778	1380/1260	80	550	18	14.6	30.7	780	9.8	248	44.2	20.1	OWL
LT265/75R16	123/120Q	E / 10	100A1777	7.5	7.0 - 8.0	3415/3085	1550/1400	80	550	18	14.6	31.9	810	10.5	267	47.4	21.5	OWL
LT285/75R16	122/119Q	D / 8	100A1775	8.0	7.5 - 8.5	3305/3000	1500/1360	65	450	18	14.6	33.1	840	11.3	286	54.4	24.7	OWL
LT235/85R16	120/116Q	E / 10	100A1773	6.5	6.0 - 7.0	3042/2778	1380/1260	80	550	18	14.6	32.0	812	9.3	235	45.8	20.8	OWL

LI Load Index SR Speed Rating (s/d) Single/Dual LR Load Range PR Ply Rating OWL Outline White Letter