

HIGHWAY ALL SEASON

Introducing

ADVENTURO HT

SATISFACTION
30 DAY
TEST DRIVE
GUARANTEE



100/80
100,000 km Limited
Warranty (P-Metric)
80,000 km Limited
Warranty (LT)

Half stated warranty
for rear of split filament



Highway Terrain



Handling



Water Evacuation



All Season



5 Year Limited
Warranty

The new Adventure HT is designed with comfort and control in mind. An advanced tread design and robust 100,000 km warranty offer the optimal balance of form and function. With features like full depth wave sipes, chamfered tread edges and a continuous center rib you can drive with confidence

and control. Adventure HT provides the grip you need, when you need it, and looks good doing it. Dual sidewall designs let you choose the perfect look for your vehicle—rugged and traditional for your pickup, or more modern for the latest SUVs.



15- 20 Inch

Speed Rating: R / S / T / H / V



50 - 85 Series

UTQG: 600 AB

Features

Benefits

Dual sidewall design

Allows two choices for the perfect look

Full depth wave sipes

Add more biting edges for improved vehicle traction on wet and snowy roads

Chamfered tread edges

Increase displacement of water to reduce the risk of hydroplaning

Continuous center rib

Provides improved braking performance and excellent stability at highway speeds

Harmonically Optimized Pitch Sequencing

Reduces road noise generation for a quieter ride

ADVENTURO HT HIGHWAY ALL SEASON

Tire Size	LI/SR	UTQG	Item Numbe	Measuring Rim	Rim Width Range	Max. Load		Max. Pressure		Tread Depth		Overall Diameter		Section Width		Weight		Side Wall
						Lbs	Kg	Psi	Kpa	32 nd	mm	Inch	mm	Inch	mm	Lbs	kg	
P235/75R15	1051	600AB	100UA3630	6.5	6.0-8.0	2028	920	44	300	11	8.4	29.0	737	9.5	242	27.5	12.5	BSW
P215/70R16	991	600AB	100UA3606	6.5	5.5-7.0	1709	775	44	300	11	8.4	28.0	711	8.8	224	23.9	10.9	BSW
P235/70R16	1041	600AB	100UA3622	7.0	6.0-8.0	1984	900	44	300	11	8.4	29.1	738	9.5	242	27.9	12.7	BSW
P245/70R16	1061	600AB	100UA3628	7.0	6.5-8.0	2094	950	44	300	11	8.4	29.6	752	9.9	251	29.4	13.3	BSW
P255/70R16	1091	600AB	100UA3627	7.5	6.5-8.5	2271	1030	44	300	11	8.4	30.2	767	10.2	260	30.4	13.8	BSW
P265/70R16	1111	600AB	100UA3624	8.0	7.0-9.0	2403	1090	44	300	11	8.4	30.7	779	10.7	272	32.5	14.8	BSW
P245/75R16	1091	600AB	100UA3626	7.0	6.5-8.0	2271	1030	44	300	11	8.4	30.6	776	9.9	252	31.2	14.1	BSW
P265/75R16	1141	600AB	100UA3632	7.5	7.0-9.0	2601	1180	44	300	11	8.4	31.7	805	10.6	269	33.2	15.1	BSW
P245/65R17	1051	600AB	100UA3623	7.0	7.0-8.5	2039	925	44	300	11	8.4	29.7	754	9.7	247	28.7	13.0	BSW
P265/65R17	1101	600AB	AS124	8.0	7.5-8.5	1060	2337	44	300	11	8.4	30.6	776	10.7	272	34.9	15.9	OWL
P245/70R17	1081	600AB	100UA3625	7.0	6.5-8.0	2205	1000	44	300	11	8.4	30.7	779	9.8	250	31.1	14.1	BSW
P265/70R17	1131	600AB	100UA3621	8.0	7.0-9.0	2535	1150	44	300	11	8.4	31.7	805	10.8	274	34.2	15.5	BSW
255/55R18	109V XL	600AB	AS125	8.0	7.0-9.0	1030	2271	50	340	11	8.4	29.0	737	10.4	265	34.0	15.4	BSW
P265/60R18	1091	600AB	AS126	7.0	6.0-7.5	1030	2271	44	300	11	8.4	30.5	775	10.7	272	35.0	15.9	OWL
P265/65R18	1121	600AB	AS127	8.0	7.5-9.5	1120	2469	44	300	11	8.4	31.5	801	10.7	272	35.8	16.3	OWL
P275/65R18	1141	600AB	AS128	8.0	7.5-8.5	1180	2601	44	300	11	8.4	32.1	815	11.0	279	38.0	17.2	BSW
P255/70R18	1121	600AB	AS129	7.5	7.0-8.0	1120	2469	44	300	11	8.4	32.1	815	10.2	260	34.4	15.6	BSW
P265/70R18	1141	600AB	AS130	8.0	7.0-9.0	1180	2601	44	300	11	8.4	32.6	829	10.7	272	38.0	17.2	OWL
P245/55R19	1031	600AB	AS131	7.0	6.0-7.5	875	1929	44	300	11	8.4	29.6	753	10.0	253	32.3	14.7	BSW
P255/60R19	108H	600AB	AS132	7.5	7.0-9.0	1000	2205	44	300	11	8.4	31.1	789	10.2	260	34.6	15.7	BSW
255/50R20	105H	600AB	AS133	8.0	7.0-9.0	925	2039	44	300	11	8.4	30.1	764	10.4	265	34.6	15.7	BSW
265/50R20	1071	600AB	AS134	8.5	8.0-9.0	975	2150	44	300	11	8.4	30.5	774	10.9	277	34.9	15.8	BSW
P255/55R20	107H	600AB	AS135	8.0	7.0-9.0	975	2419	44	300	11	8.4	31.0	788	10.4	265	33.3	15.1	BSW
P275/55R20	111H	600AB	100UA3601	8.5	7.5-9.5	2403	1090	44	300	11	8.4	31.9	810	11.2	284	36.5	16.6	BSW
P275/60R20	114H	600AB	AS136	8.0	7.5-9.5	1180	2601	44	300	11	8.4	33.0	838	11/0	279	39.0	17.7	BSW
L1225/75R16	115/112S	E	AS137	7.0	6.0-7.5	1215/1120	2680/2470	80	550	10.2	8.1	29.3	744	8.8	223	37.1	16.8	BSW
L1245/75R16	120/116S	E	AS138	7.0	6.5-8.0	1380/1260	3042/2778	80	550	10.2	8.1	30.5	774	9.8	248	41.8	19.0	BSW
L1265/75R16	123/120S	E	AS139	7.0	6.0-7.5	1550/1400	3415/3085	80	550	10.2	8.1	31.7	804	10.5	267	47.5	21.5	OWL
L1235/85R16	120/116S	E	AS140	6.5	6.0-7.5	1380/1260	3042/2778	80	550	10.2	8.1	31.7	806	9.3	235	42.9	19.5	BSW
L1265/70R17	121/118S	E	AS141	8.0	7.0-8.5	1450/1320	3195/2910	80	550	10.2	8.1	31.7	804	10.7	272	46.9	21.3	OWL
L1245/75R17	121/118S	E	AS142	7.0	6.0-7.5	1450/1320	3195/2910	80	550	10.2	8.1	31.5	800	9.8	248	44.4	20.2	BSW
L1235/80R17	120/117R	E	AS143	6.5	6.0-7.0	1400/1285	3085/2835	80	550	10.2	8.1	31.8	808	9.3	235	42.8	19.5	BSW

LI Load Index **SR** Speed Rating **XL** Extra Load **UTQG** Uniform Tire Quality Grade **BSW** Black Side Wall

