

COMMERCIAL VAN ALL SEASON

Introducing

MAXMILER Pro



The new Maxmiler Pro is designed for today's light commercial vehicles like Ford Transit, Nissan NV and RAM ProMaster. This durable tire is built to carry the heavy loads of compact and full-size multi-purpose vans. The tread pattern delivers

all season performance for highway use with the toughness needed for off-road driving near the jobsite. Maxmiler Pro—your partner in business to get the job done.



15 - 17 Inch



Speed Rating: Q / R / T / H



55 / 60 / 65 / 75 / 80 / 85 Series

M + S

Features

Benefits

Square tread footprint

Results in even pressure distribution which resists irregular wear and improves tire mileage

Large shoulder blocks with integrated sipes

Improve cornering, stability, braking and wet/dry grip

Wide tread grooves

Enhance water evacuation for excellent hydroplaning resistance

Reinforced sidewall construction

Provides the heavy load carrying capacity needed for commercial multi-purpose vans

Low rolling resistance

Reduces fuel consumption

MAXMILER Pro

COMMERCIAL VAN ALL SEASON



Tire Size	LI / SR	UTQG	Item Number	Measuring Rim	Rim Width Range	Max. Load		Max. Pressure		Tread Depth		Overall Diameter		Section Width		Weight		Side Wall
				inch	inch	lbs	kg	psi	kpa	32 nd	mm	inch	mm	inch	mm	lbs	kg	
185/60R15C	94/92T	-	B623	5.5	5.5 - 6.0	1477/1389	670/630	55	375	12	9.2	23.7	603	7.4	188	21.1	9.6	BSW
P205/65R15	95T XL	700 AA	B624	6.0	5.5 - 7.5	1521	690	50	340	11	8.7	25.5	647	8.2	209	24.6	11.2	BSW
215/55R16	97H XL	700 AA	B625	7.0	6.0 - 7.5	1609	730	50	340	11	8.7	25.3	642	8.9	226	25.3	11.5	BSW
235/65R16C	121/119R	-	B626	7.0	6.5 - 7.5	3195/3000	1450/1360	85	575	13	10.6	28.0	712	9.4	240	37.3	16.9	BSW
225/75R16C	121/120R	-	B627	6.0	6.0 - 7.0	3195/3085	1450/1400	85	575	13	10.7	29.3	744	8.8	223	37.9	17.2	BSW

Tire Size	LI / SR (s/d)	LR / PR	Item Number	Measuring Rim	Rim Width Range	Max. Load (s/d)		Max. Pressure		Tread Depth		Overall Diameter		Section Width		Weight		Side Wall
				inch	inch	lbs	kg	psi	kpa	32 nd	mm	inch	mm	inch	mm	lbs	kg	
LT245/75R16	120/116Q	E / 10	B631	7.0	6.5 - 8.0	3042/2778	1380/1260	80	550	14	11.2	30.5	774	9.8	248	42.2	19.2	BSW
LT215/85R16	115/112Q	E / 10	B628	6.0	5.5 - 7.0	2680/2470	1215/1120	80	550	13	10.2	30.4	772	8.7	222	40.5	18.4	BSW
LT235/85R16	120/116R	E / 10	B630	6.5	6.0 - 7.5	3042/2778	1380/1260	80	550	13	10.7	31.7	806	9.3	235	42.1	19.1	BSW
LT245/75R17	121/118R	E / 10	B632	7.0	6.5 - 7.5	3195/2910	1450/1320	80	550	14	11.2	31.5	800	9.8	248	45.1	20.5	BSW
LT235/80R17	120/117R	E / 10	B629	6.5	6.0 - 7.5	3085/2835	1400/1285	80	550	13	10.7	31.8	808	9.3	235	43.9	19.9	BSW

LI Load Index SR Speed Rating XL Extra Load UTQG Uniform Tire Quality Grade (s/d) Single/Dual LR Load Range PR Ply Rating BSW Black Side Wall

Square Tread Footprint
Even pressure distribution resists irregular wear and improves tire mileage

Wide Tread Grooves
Enhance water evacuation for excellent hydroplaning resistance

Reinforced Sidewall Construction
Heavy load carrying capacity for commercial multi-purpose vans

Large Shoulder Blocks with Integrated Sipes
Improve cornering, stability, braking and wet/dry grip

