

TRAILER SERVICE



MAXMILER ST




Maxmiler ST is a specially designed trailer tire with stiff sidewall construction to help reduce trailer

sway and enhanced load carrying capacity for stable and reliable towing.

 13 - 16 Inch

 Speed Rating: M

 75 - 85 Series

M + S

Features

Benefits

Full width tread

Results in better road contact, strong grip, better maneuverability and braking performance

Dual high modulus steel belts

Enhance handling and stability and improve puncture resistance

Strong shoulder block design

Increases traction and stability

High technology polyester casing

Offers high durability and improved stability

Nylon jointless belt edge strips

Increases strength and treadwear

MAXMILER ST

TRAILER SERVICE



Tire Size	LI / SR (s/d)	LR / PR	Item Number	Measuring Rim	Rim Width Range	Max. Load (s/d)		Max. Pressure		Tread Depth		Overall Diameter		Section Width		Weight		Side Wall
				inch	inch	lbs	kg	psi	kpa	32 nd	mm	inch	mm	inch	mm	lbs	kg	
ST175/80R13	91/87M	C / 6	100A2778	5.0	4.5 - 5.5	1360/1200	615/545	50	350	10	7.9	24.0	610	7.0	177	16.6	7.5	BSW
ST205/75R14	100/96M	C / 6	100A2779	5.5	5.0 - 6.0	1760/1570	800/710	50	350	10	7.9	26.1	664	8.0	203	22.5	10.2	BSW
ST215/75R14	102/98M	C / 6	100A2781	6.0	5.5 - 7.0	1870/1650	850/750	50	350	11	8.7	26.7	678	8.5	216	24.3	11.0	BSW
ST205/75R15	107/102M	D / 8	100A2780	5.5	5.0 - 6.5	2150/1870	975/850	65	450	10	7.9	27.1	689	8.0	203	24.8	11.3	BSW
ST225/75R15	117/112M	E / 10	100A2782	6.0	6.0 - 7.0	2830/2470	1285/1120	80	550	11	8.7	28.3	719	8.8	223	31.4	14.3	BSW
ST235/80R16	123/119M	E / 10	100A2783	6.5	6.0 - 7.5	3420/3000	1550/1360	80	550	16	12.6	30.8	782	9.3	235	40.6	18.4	BSW
ST235/85R16	125/121M	E / 10	100A2784	6.5	6.0 - 7.0	3640/3200	1650/1450	80	550	16	12.6	31.7	806	9.3	235	42.7	19.4	BSW

LI Load Index SR Speed Rating (s/d) Single/Dual LR Load Range PR Ply Rating BSW Black Side Wall

